

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,106,821 B2
APPLICATION NO. : 09/804744
DATED : September 12, 2006
INVENTOR(S) : Takashi Usui et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title Page Item (57)


The Abstract should read --A data modulation method and a data modulation device and a communication device are provided in which a reference symbol is optimized in order to contain the structure of "IA-A-IA-A-A-IA-A-IA-IA" and is allocated to sub-carriers of an OFDM symbol. More specifically, by designing the structure of a preamble of the time domain, distinction from other communication systems is achieved along with clock synchronization. Also, a series having a low peak average ratio and a dynamic range has been adopted for the sync symbol used in the OFDM. Since generation and detection processing can be conducted utilizing a generation device and a detection device of the sync preamble used in a conventional system, this system has an advantage in increasing the common use of an LSI chip. The sync series is divided into 2 parts, A and B, rather than to one B region and has a simple construction.--

Column 10, Line 39, "Flow" should read --F_{pow}--;

Column 13, Line 21, "TEEE802" should read --IEEE802--

Signed and Sealed this

Twenty-first Day of August, 2007



JON W. DUDAS
Director of the United States Patent and Trademark Office